



- Surface Mount (Ceiling)
- White Polycarbonate body
- Translucent Polycarbonate Cover
- Extra Long Life LiFePO4 cells
- Ingress Protection Rating - IP65
- DDP (Deep Discharge Protection)
- Cree LED's
- Perfect for Warehouse Applications
- LDT Files Available upon Request

A stylish and compact circular IP65 3 Watt or 6 Watt LED Bulkhead suitable for ceiling mounting applications. The 3W unit is available in either Switchable Maintained, Non-Maintained or as DALI Self-Test (2W only). The 6W unit is offered as non-maintained only. Either 273 lumen (2W), 390 delivered lumen (3W) or 600 delivered lumen (6W) this is an excellent solution for tall ceiling heights in damp locations. The unit utilises LiFePO4 battery technology which provides a far longer life than traditional battery types, making this an ideal product for difficult to maintain areas.

Order Codes

CB3S/3W/M3	CB3S/6W/NM3	CB3S/2W/DA
3W Non-Maintained	6W Non-Maintained	3W DALI Self-Test
3W Maintained		Mains Switch Maintained

Technical Details:

Mains Supply	230-240V AC 50/60 Hz	230-240V AC 50/60 Hz	230-240V AC 50/60 Hz
Power Rating Maintained	55mA $\lambda = 0.6$		
Power Rating Non-Maintained	25mA $\lambda = 0.6$	25mA $\lambda = 0.6$	16mA $\lambda = 0.48$
Duration	3 Hours	3 Hours	3 Hours
Recharge Period	12 Hours – Electronic	12 Hours – Electronic	24 Hours
Battery Size & Type	6.4V 3.0Ah LiFePO4 Cells	6.4V 6.0Ah LiFePO4 Cells	9.6V 1.5Ah LiFePO4 Cells
Charge Current	0-400mA Dual Rate	0-400mA Dual Rate	0-150mA Dual Rate
Ingress Protection Rating	IP65	IP65	IP65
Light Output	3 Watts	6 Watts	2 Watts
Light Source	1 x 3 Watt Cree LED	1 x 6W Cree LED	1 x 3W Cree LED
Lumen Output	390 Delivered Lumen	600 Delivered Lumen	273 Delivered Lumen
Weight	0.80Kg	0.88Kg	0.81Kg