





Technical Details:

Dimensions:

Nominal Voltage (V)	6.4 Volts	Length and Width	160mm x 34.5mm	
Nominal Capacity	3.8Ah @ 25°C	Fixing Centres	Hook Eye	
Rated Wh	24.3Wh	Weight	275 g	
Standard Charging Current	360mA			
Standard Discharge Current	950mA to 5V			
Charging Cut-off Voltage	7.1V			
Temperature:			UN 3481 For more information, call	
Standard Temperature Range	0	to + 60°C	We advise that when shipping these	
Storage (within 1 Year)	0	to + 25°C	batteries by air, that IATA regulation UN3481 PI966 is followed. This states	
There is 1 version available -			that the battery must be packed with its associated control gear and the	
Order Codes			above label must appear on the outer packaging.	
2/LP38/PT/MS	6.4V 3.8Ah Encased LiFePO4 Battery and Molex Connector			

This battery features a protection circuit module (PCM) that regulates the current between cells and protects the battery from any potential short circuit situations.



Batteries supplied with leads are fitted with an irreversible socket & 20cm of cable. ENSURE CORRECT POLARITY

) LiFepol 🖄 🤇 🗧 🛛 🗰

Tel +44 (0)1708 372223 | www.liteplan.com | customerservice@liteplan.com | RM3 0AP, UK

Liteplan reserve the right to change colour, price or specification without prior notice