



- Surface Mount
- White Polycarbonate body
- Extra Long Life LiFePO4 cells
- Ingress Protection Rating - IP65
- DDP (Deep Discharge Protection)
- Samsung LED's
- Kit of Legends for Ease of Stocking
- 25m Viewing Distance
- Basic, or DALI-2 Self-test Operation

A stylish and compact IP65 rated 3 Watt LED exit sign suitable for wall mounting. The unit is available as either a Switchable Maintained, Non-Maintained or a Switchable Maintained DALI-2 Self-Test version. The fitting is not only more compact than the majority of LED exit signs, but offers an ingress protection of IP65 and a kit of legends for ease of installation and stocking.

The batteries used with this unit not only offer double the life of traditional emergency lighting batteries, but consume far less power during their operation.

## Order Codes

CE5S/3W/M	Mains Switchable Maintained IP65 Wall mounted Exit Sign
CE5S/3W/NM	Non-Maintained IP65 Wall Mounted Exit Sign
CE5S/3W/DA	Mains Switchable Maintained DALI-2 Self-Test IP65 Wall Mounted Exit Sign

## Technical Details:

	CE5S/3W/M3	CE5S/3W/DA
Mains Supply	230-240V AC 50/60 Hz	
Power Rating	55mA $\lambda = 0.6$ Maintained 25mA $\lambda = 0.6$ Non-maintained	40mA $\lambda = 0.6$ Maintained 16mA $\lambda = 0.48$ Non-maintained
Duration	3-Hours	
Recharge Period	24-Hours	
Battery Size & Type	M3 = 6.4V 3.0Ah LiFePO4 Cells	3.2V 4.5Ah LiFePO4 Cells
Charge Current	225mA Nominal	
Ingress Protection Rating	IP65	
Light Source	8 pcs Samsung LED	
Possible Arrow Configurations	Arrow Up, Arrow Down, Arrow Left & Arrow Right	