



- Ready for Connection to Casambi Surface Mount (Wall or Ceiling)
- White Polycarbonate Body
- Extra Long Life LiFePO₄ cells
- Ingress Protection Rating - IP20
- 25m viewing distance
- ISO7010 legends as standard
- DDP (Deep Discharge Protection)
- Samsung LED's
- TM65.2 Rating of 14.98kg CO₂e

A stylish and compact Double Sided LED Exit Sign suitable for either wall or ceiling mounting. The unit is available in either a Switchable Maintained or Non-Maintained operation and is ready to connect to the Casambi Wireless platform. The fitting is supplied with a PMMA screen printed legend plate which offers an impressive 25m viewing distance.

The legend panels are available in either Arrow Up (AU), Arrow Down (AD) or Arrow Left/Right (ALAR). Please note that all legends are single sided, apart from the ALAR which are double sided. The batteries used with this unit not only offer double the life of traditional emergency lighting batteries, but consume far less power during their operation.

Order Codes

CE1S/CASAMBI/** Casambi Ready Switchable Maintained Ceiling or Wall Mounted Blade Exit Sign

** Please specify legend required AU, AD, or ALAR

Technical Details:

Mains Supply	230-240V AC 50/60 Hz
Power Rating Charging M-Mode *	5.4W 30mA $\lambda = 0.75$
Power Rating Charged NM-Mode *	0.3W 8mA $\lambda = 0.15$
Duration	3-Hours
Recharge Period	24-Hours
Battery Size & Type	3.2V 3.8Ah LiFePO ₄ Cells
Charge Current	225mA nominal
Ingress Protection Rating	IP40
Weight	0.92Kg

* Following its initial charge, the unit will spend 90% of its operational life in standby mode