





## Technical Details:

## **Dimensions:**

Nominal Voltage (V)	12.8 Volts	Length and Width	175mm x 60mm x 42mm
Nominal Capacity	3.8Ah @ 25°C	Fixing Centres	Hook Eye
Rated Wh	48.6Wh	Weight	456 g
Standard Charging Current	450mA		. <u></u>
Standard Discharge Current	900mA to 11.8V		
Charging Cut-off Voltage	13.2V		
Temperature:			UN 3481 For more information, call
Standard Temperature Range	0 t	co + 60°C	We advise that when shipping these
Storage (within 1 Year)	0 to + 25°C		batteries by air, that IATA regulation UN3481 PI966 is followed. This states
There is 1 version available -			that the battery must be packed with its associated control gear and
Order Codes			the above label must appear on the outer packaging.

```
4/LP38/PT/TE
```

12.8V 3.8Ah Encased LiFePO4 Battery and TE Connector

This battery features a protection circuit module (PCM) that regulates the current between cells and protects the battery from any potential short circuit situations. The battery also features temperature monitorring via the yellow cable.



Batteries supplied with leads are fitted with an irreversible socket & 20cm of cable. ENSURE CORRECT POLARITY

Tel +44 (0)1708 372223 | www.liteplan.com | customerservice@liteplan.com | RM3 OAP, UK

Liteplan reserve the right to change colour, price or specification without prior notice