



Technical Details:

Nominal Voltage (V) 3.2 Volts **Nominal Capacity** 3.8Ah @ 25°C Rated Wh 12.2Wh Standard Charging Current 360mA Standard Discharge Current 720mA to 2.5V Charging Cut-off Voltage 3.65V

Dimensions:

Length and Width	90mm x 34.5mm
Fixing Centres	Hook Eye
Weight	141 g

Temperature:

Standard Temperature Range	0 to + 60°C
Storage (within 1 Year)	0 to + 25°C

There is 1 version available -

Order Codes

1/LP38/PT/MS

Storage (within 1 Year)	0 to -
storage (within Frear)	0 10

3.2V 3.8Ah Encased LiFePO4 Battery and TE Connector



We advise that when shipping these batteries by air, that IATA regulation UN3481 PI966 is followed. This states that the battery must be packed with its associated control gear and the above label must appear on the outer packaging.

This battery features a protection circuit module (PCM) that regulates the current between cells and protects the battery from any potential short circuit situations. The battery also features temperature monitorring via the yellow cable.



Batteries supplied with leads are fitted with an irreversible socket & 20cm of cable. **ENSURE CORRECT POLARITY**

Tel +44 (0)1708 372223 www.liteplan.com | customerservice@liteplan.com

Liteplan reserve the right to change colour, price or specification without prior notice



