





Technical Details:

| Nominal Voltage (V) | 12.8 Volts |
|----------------------------|----------------|
| Nominal Capacity | 3.8Ah @ 25°C |
| Rated Wh | 48.6Wh |
| Standard Charging Current | 450mA |
| Standard Discharge Current | 900mA to 11.8V |
| Charging Cut-off Voltage | 13.2V |

Dimensions:

| Length and Width | 175mm x 60mm x 42mm |
|------------------|---------------------|
| Fixing Centres | Hook Eye |
| Weight | 456 g |

Temperature:

| Standard Temperature Range | 0 to + 60°C |
|----------------------------|-------------|
| Storage (within 1 Year) | 0 to + 25°C |

There is 1 version available -

UN 3481

We advise that when shipping these batteries by air, that IATA regulation UN3481 PI966 is followed. This states that the battery must be packed with its associated control gear and the above label must appear on the outer packaging.

Order Codes

4/LP38/PT/TE 12.8V 3.8Ah Encased LiFePO4 Battery and TE Connector

This battery features a protection circuit module (PCM) that regulates the current between cells and protects the battery from any potential short circuit situations. The battery also features temperature monitorring via the yellow cable.



Batteries supplied with leads are fitted with an irreversible socket & 20cm of cable.

ENSURE CORRECT POLARITY

Tel +44 (0)1708 372223 | www.liteplan.com | customerservice@liteplan.com | RM3 0AP, UK





