



- Ready for Connection to MyMesh
- Surface Mount (Wall)
- White Polycarbonate Body
- Extra Long Life LiFePO4 cells
- Ingress Protection Rating - IP20 rated
- 30m Viewing Distance
- ISO7010 Legends as Standard
- DDP (Deep Discharge Protection)
- Samsung LED's
- Supplied With a Kit of Legends
- TM65.2 Rating of 21.46kg CO<sub>2</sub>e
- Features Battery Temperature Protection

A stylish and compact wall mounting Single Sided LED Exit Sign that can either be surface or semi-recesses mounted. The unit is available in either a Switchable Maintained or Non-Maintained operation and is ready to connect to the MyMesh Wireless platform.

The unit comes with a PMMA legend which offers an impressive 30m viewing distance.

The luminaire is supplied with a pack of inlay panels which includes Arrow Down (AD), Arrow Left (AL), Arrow Right (AR) and Arrow up (AU).

The charger will cut-off if the Tc of the battery falls below 0 degrees C or above 55 degrees C. The product will however operate when required in emergency, should there be enough capacity remaining in the battery.

## Order Codes

**CE2S/MYMESH**

MyMesh Ready Switchable Maintained Wall Mounted Exit Sign

## Technical Details:

Mains Supply	230-240V AC 50/60 Hz
Power Rating Charging M-Mode *	5.4W 30mA $\lambda = 0.75$
Power Rating Charged NM-Mode*	0.3W 8mA $\lambda = 0.15$
Duration	3-Hours
Recharge Period	24-Hours
Battery Size & Type	3.2V 3.8Ah LiFePO4 Cells
Charge Current	225mA nominal
Ingress Protection Rating	IP40
Weight	1.3Kg

\* Following its initial charge, the unit will spend 90% of its operational life in standby mode