



The CBP is supplied either as a changeover module, which can be mounted away from the luminaire.

- Static Inverter Changeover Module
- Suitable for 50V, 110V or 240V DC Systems
- Suitable for 240V AC Systems
- Holds Power from the Primary of the Driver
- Inhibits the Dimming State of the Load
- Supplied in IP54 Remote Enclosure

Emergency lighting change over relays with an additional dimming inhibition relay that will restore a fitting that was running in a mains dimmed state, to full brightness for emergency operation.

Compatible with fluorescent and LED loads and runs in conjunction with either 240V 50/60Hz AC static inverter or 50V, 110V or 240V DC central battery systems.

**NB:** The associated control gear must be capable of operating from the emergency voltage.

## Order Codes

<b>CBP/WP100/R</b>	Supplied as a changeover module for integral mounting within a luminaire
<b>CBP/NEON/G</b>	Although not essential, a 240V AC/DC neon is available for fitting indication

## Technical Details:

Emergency Voltage from Static Inverter	240V AC (50/60Hz)
Emergency Voltage from Central Battery	50V, 110V or 240V DC
Tc Temperature and Point	50°C Top Centre
Ambient Temperature	0°C - 35°C
Mains Supply	230-240V AC 50/60Hz
Changeover Relay Rating	3A 240V
Power Rating	2.0W 14mA $\lambda = 0.58$
Remote Enclosure Dimensions	250mm x 80mm x 70mm
Module Weight	0.38Kg