



- Suitable for Remote Applications
- Compatible with DALI Emergency Products
- Simple Installation
- Casambi Ready Active Node
- Cable Strain relief
- Requires a 41mm Aperture
- Includes DALI Power Supply

The CAB/1/R is designed to convert a standard emergency DALI product to become Casambi Ready. Connections are made to the emergency control gear via a simple DALI+/DALI- pair.

The module is capable of being used for integral, or remote applications, thanks to its removable strain relief terminal covers.

The CAB/1/R measures 98mm long x 33.7mm wide x 25.5mm high.

## Order Codes

**CAB/1/R** Casambi Enabled Wireless Node for Connection to DALI Emergency Control Gear

## Technical Details:

Input Voltage	230-240V AC 50/60Hz 0.3A
DALI PS Consumption	Irated - 80mA / Imax - 250mA
Range (indoor)	Up to 50m line of sight
Technology	Proprietary BLE Mesh (Bluetooth Low Energy)
IP Rating	IP20
Frequency	2.4 GHz ISM Band
T <sub>a</sub>	-20° C to +60° C
T <sub>c</sub>	75° C
Output Control	DALI-2

Liteplan declares that the radio equipment type CAB/1 is in compliance with Directive 2014/53/EU. The full text of the EU declaration of conformity is available at [liteplan.com](http://liteplan.com)